

Pistolete pentru sudare mecanizata WIG

Pistolete pentru sudare mecanizata WIG racire aer si lichid



ABITIG® 150 MT
ABITIG® 260 W MT

Consumabile identice cu cele ale
ABITIG® 150 / ABITIG® 260 W –
vezi pag. 57.



■ **ABITIG® 200 MT / 300 W MT**
cu electrod Wolfram ajustabil

ABITIG® 200 MT
ABITIG® 300 W MT
ABITIG® 400 W MT

Consumabile identice cu cele ale
ABITIG® 200 / ABITIG® 450 W –
vezi pag. 59.

WIG



ABITIG® 500 W MT

Consumabile la cerere.

| Date tehnice (EN 60 974-7) | | | | Electrod | Nr. art. |
|----------------------------|--------|---------------------|------|--------------|-------------|
| Tip | Racire | Curent | D.A. | Wolfram ø | Corp pistol |
| ABITIG® 150 MT | aer | 150 A DC / 110 A AC | 60% | 1.0 – 3.2 mm | 778.1020 |
| ABITIG® 260 W MT | lichid | 260 A DC / 180 A AC | 100% | 1.0 – 3.2 mm | 779.1020 |
| ABITIG® 200 MT | aer | 200 A DC / 140 A AC | 60% | 1.6 – 3.2 mm | 778.2020 |
| ABITIG® 300 W MT | lichid | 300 A DC / 210 A AC | 100% | 1.6 – 4.0 mm | 779.2020 |
| ABITIG® 400 W MT | lichid | 400 A DC / 280 A AC | 100% | 1.6 – 4.8 mm | 779.4020 |
| ABITIG® 500 W MT | lichid | 500 A DC / 350 A AC | 100% | 1.6 – 6.4 mm | 779.6020 |

Pentru comanda unui pistol complet, va rugam specificati lungimea pachetului de furtune si tipul cuplarii la echipament.